

# noVus


## Bullet IP Camera

NVIP-5H-6201-II/7043



6000 VSS IP

### FUNCTIONS



### KEY FEATURES

- Resolution: 5 MPX
- Lens: fixed focal, f=2.8 mm/F1.6
- MicroSD card support
- D/N function - IR cut filter
- Video content analysis
- microSD card support
- WDR with double scan sensor
- Min. Illumination from 0.007 lx (0 lx, IR on)
- IR LED, range up to 30 m

### DIMENSIONS



|  |   |
|--|---|
| <b>Image</b>                             |   |
| Image Sensor                             | 5 MPX CMOS sensor 1/2.7" SmartSens  |
| Number of Effective Pixels               | 2884 (H) x 1624 (V)   |
| Min. Illumination                        | 0.007 lx/F1.6 - color mode,<br>0 lx (IR on) - B/W mode  |
| Electronic Shutter                       | auto: 1/2 s ~ 1/100000 s  |
| Digital Slow Shutter (DSS)               | up to 1/3 s   |
| Wide Dynamic Range (WDR)                 | yes (double scan sensor), 120dB   |
| Digital Noise Reduction (DNR)            | 2D, 3D  |
| Highlight Compensation (HLC)             | yes   |
| Back Light Compensation (BLC)            | yes   |
| Reduction of image flicker (Antiflicker) | yes   |
| <b>Lens</b>                              |   |
| Lens Type                                | fixed focal, f=2.8 mm/F1.6  |
| <b>Day/Night</b>                         |   |
| Switching Type                           | mechanical IR cut filter  |
| Switching Mode                           | auto, manual, time  |
| Switching Level Adjustment               | yes   |
| Switching Delay                          | 2 ~ 120 s   |
| Switching Schedule                       | yes   |
| Visible Light Sensor                     | yes   |
| <b>Network</b>                           |   |
| Stream Resolution                        | 2880 x 1620, 2560 x 1440 (QHD), 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 704 x 480, 640 x 480 (VGA), 480 x 240, 352 x 288 (CIF), 352 x 240 |
| Frame Rate                               | 30 fps for each resolution  |
| Multistreaming Mode                      | 3 streams   |
| Video/Audio Compression                  | H.264, H.264+, H.265, H.265+, MJPEG/G.711   |
| Number of Simultaneous Connections       | max. 10   |
| Bandwidth                                | 60 Mb/s in total  |
| Network Protocols Support                | HTTP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, RTMP   |
| ONVIF Protocol Support                   | Profile S   |
| Camera Configuration                     | from Internet Explorer browser<br>languages: Polish, English, and others  |
| Compatible Software                      | NMS, N Control 6000   |
| Mobile applications                      | SuperLive Plus (iPhone, Android)  |
| <b>Other functions</b>                   |   |
| Privacy Zones                            | 4 video mask type: single color   |
| Motion Detection                         | yes   |
| Region of interest (ROI)                 | 8   |
| Video Content Analysis (VCA)             | abandoned object, object disappearance, line cross, Scene Change, intrusion detection   |
| Image Processing                         | sharpening, mirror effect, corridor mode, vertical flip, horizontal flip  |
| Prealarm/Postalarm                       | up to 6 s/up to 120 s   |
| System Reaction to Alarm Events          | e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card   |
| Restoring default settings               | via web browser, using reset button, via NMS IPTool software  |
| <b>IR LED</b>                            |   |
| LED Number                               | 1   |
| Range                                    | 30 m  |
| Smart IR                                 | yes (software support)  |
| <b>Interfaces</b>                        |   |
| Audio Input/Output                       | 1 x Jack (3.5 mm)/- built-in microphone   |
| Network Interface                        | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s   |
| Memory Card Slot                         | microSD - capacity up to 256GB  |
| <b>Installation parameters</b>           |   |
| Dimensions (mm)                          | with bracket: 74.5 (W) x 74.5 (H) x 167.5 (L)   |
| Weight                                   | 0.4 kg  |
| Degree of Protection                     | IP 67 (details in the user's manual)  |
| Enclosure                                | aluminium, grey, fully cable managed wall mount bracket in-set included, IK10 impact rating   |
| Power Supply                             | 12 VDC, PoE (IEEE 802.3af, Class 3)   |
| Surge protection                         | TVS 4000 V  |
| Power Consumption                        | 3.5 W,<br>6 W (IR illuminator on)   |
| Operating Temperature                    | -30°C ~ 60°C  |
| Humidity                                 | max. 95% relative (non-condensing)  |